


# MODEL MHT60-1 HIGH TEMP REFRIGERATED AIR

MECHANICAL SPECS	
Inlet Air Flow	60 SCFM
Inlet Pressure	150 PSIG
Inlet Temp	180 F
DEWPOINT TEMP	38 F
COOLING AIR FLOW	230 CFM
PRESSURE LOSS, DESIGN	2.7
CONDENSER TYPE	Air Cooled
WEIGHT	180 LBS
IN & OUT CONNECTION	1" FPT
DRAIN CONNECTION	1/4" FPT
MAXIMUM AMBIENT TEMP	110 F
MINIMUM AMBIENT TEMP	40 F
MAXIMUM AIR PRESSURE	232 PSIG
ELECTRICAL SPECS	
Locked Rotor Amps	40
Rated Load Amps	8.2
Max Fuse	15
Power Connection	115-1-60
Full Load Power (WATTS)	935



## OPTIONAL FEATURES

- Pre-filter and after-filters mounted on the dryer
- 230-1-60 voltages
- Additional pressure and temperature gauges
- Mounting Brackets

## STANDARD FEATURES

- Aluminum block heat exchanger
- Air to air pre-cooler/re-heater
- Stainless Steel mesh separator
- Tecumseh Compressor
- Suction Pressure Gauge
- On-Off Switch
- Compressor Overload
- Heavy duty industrial powder coated steel cabinet
- Environmentally friendly R134a refrigerant
- Refrigerant access ports
- Expansion valve
- Hot Gas Bypass Valve
- Filter Drier
- Programmable electronic drain valve with y-strainer
- Easy access cabinet design allows for ease of service.
- 9 foot power cord and plug
- Made In USA



4123 PIONEER DR  
WALLED LAKE, MI USA  
48390

248-624-6300  
248-624-0622 FAX  
sales@macair1.com  
www.macair1.com